

MI Thermocouple & RTD Units



Thermal Resources Management LTD

TEMPERATURE HOUSE

21 Sedling Road
Wear Industrial Estate
Washington
Tyne & Wear
NE38 9BZ
United Kingdom

Tel.: +44(0)191 4168884
Fax: +44(0)191 4192345
Email: sales@trmltd.co.uk

RTD Data Sheet - Standard 3 & 4 Wire Assembly

To order please specify the following:

1. Part reference (see example below).
2. Design lengths usually specified in mm, including immersion or route length and tail length (see illustration).
3. Tail type (see table 3).
4. Seal type (see table 4).
5. Any accessories required e.g. Termination gland as illustrated.

Part Reference Example:

See table 1 for cables and specifications

P 4 D - 316L - 60

- Categorise Probe
- Number of Conductors
- Conductor Material
- Sheath Material
- Overall Cable Diameter x 10 (Metric)

Temperature °C	Class A		Class B	
	± °C	± Ω	± °C	± Ω
-200	0.55	0.24	1.3	0.56
-100	0.35	0.14	0.8	0.32
0	0.15	0.06	0.3	0.12
100	0.35	0.13	0.8	0.30
200	0.55	0.20	1.3	0.48
300	0.75	0.27	1.8	0.64
400	0.95	0.33	2.3	0.79
500	1.15	0.38	2.8	0.93
600	1.35	0.43	3.3	1.06
650	1.45	0.46	3.6	1.13
700	-	-	3.8	1.17
800	-	-	4.3	1.28
850	-	-	4.6	1.34

Sheath Material	Conductor Material	RTD Category	Cable Diameter	Tolerance Class
C = Copper	C = Copper	R = Premium Grade	4.5mm (45)	A = Class A
D = Cupro Nickel	D = Nickel	T = Commercial Grade	6.0mm (60)	B = Class B
T = 316L	R = Nickel-Chrome			
S = 321				

Type	Configuration	Colour Code
PTFE Insulated Flexible	3 Wire	2 Red & 1 White
	4 Wire	2 Red & 2 White
PTFE Insulated Solid	3 Wire	2 Red & 1 White
	4 Wire	2 Red & 2 White
	3 Wire & Earth tail	2 Red, 1 White & 1 Green/Yellow

Fitting	Type	Tail Type
Orimp	Plain	3 Wire flexible
	Plain	4 Wire flexible
Silver Solder	Plain	3 Wire solid
		4 Wire solid
	Earth Tail	3 Wire & Earth tail solid

Reference	Material	Tail Type
TGMV 45 16	Brass	16mm ISO Metric
TGMV 60 16		
TGMV 45 20		20mm ISO Metric
TGMV 60 20		
TGMVS 45 16	Stainless Steel	16mm ISO Metric
TGMVS 60 16		
TGMVS 45 20		20mm ISO Metric
TGMVS 60 20		

Pressure entry fittings e.g. BSPT are also available on request

Notes.

RTD probes manufactured to IEC751.

Tolerance classes are to BS1904:1984-IEC751:1983.

Minimum immersion length = 100mm.

Standard tail length = 150mm

Maximum operating temperature = 550°C

Minimum operating temperature: Grade A = -196°C
Grade B = 0°C

